



PostBase® insight Semi-Auto

PostBase[®] insight Semi-Auto The perfect mailing system for small offices

The PostBase[®] insight semi-auto is a fully IMI-compliant postage meter with the latest innovation in mailing system technology. This fully digital mailing system boasts a full color adjustable touchscreen, intuitive interface and seamless connectivity for postage download and software updates. Gain access to postal discounts and complementary software solutions that make the PostBase[®] insight a smooth operating workhorse for your business.



USPS® IMI Approved Postage Meter



The PostBase[®] insight is equipped with the most up-to-date USPS[®] Intelligent Mail Indicia (IMI) technology. The PostBase[®] insight has been designed to fully meet all USPS[®] standards and requirements.



High Yield Ink - Low Cost Per Imprint

PostBase® insight is designed to keep your operational costs low. With a high yield, dual ink cartridge system, it offers the lowest cost per imprint in its class. Ink cartridge replacement is easy; users are guided through the process with on-screen animation.



Convenient & Professional

- Postage available 24/7
- Metered mail discounts
- Full set of USPS[®] postal rates
- Intuitive touchscreen operation
- Long lasting, high capacity ink cartridges
- Professional business mail image

FP Parcel Shipping Ship. Track. Save.

Paired with the PostBase® insight, FP Parcel Shipping is the perfect companion to send packages. FP Parcel Shipping comes equipped with the USPS® shipping rates with the option to add multi-carrier shipping, giving you the power to select the best rate for the day you want your package to arrive.

Saving time and money while sending packages has never been simpler. This online shipping application allows you to easily compare rates and print shipping labels with the tracking barcodes for the carrier and service selected.

FP Parcel Shipping also offers:

- Discounted Commercial Plus® Pricing
- Free insurance on Priority Mail[®] and Priority Mail Express[®] (up to \$100 value)
- CASS address correction and validation
- Package tracking dashboard with email notifications
- Multi-carrier rate shopping option add-on





TT

Label Printer (optional)

External Scale (optional)



Prints IMpb compliant tracking labels on letter size paper or 4" x 6" thermal shipping labels



Features

Adjustable touchscreen Rates up to 5 lbs. with integrated scale Prints up to 25 letters per minute Cost Account tracking - 5 accounts Cost Account printing Quick select rate shortcuts - 4 shortcuts Rate Wizard for selecting USPS® Postal Products Full set of USPS® rates and Extra Services Automatic postal rate downloads Envelope moistener Envelope graphics - 6 std., 2 custom PIN code access protection High speed internet connection (LAN) Easy ink replacement FP Parcel Shipping online application - USPS®

Connected to FP online

FP offers an easy way to get an overview of your mailing system, access your invoices and orders, and purchase postage and supplies all from a single online platform. Plus, find product specific support and access to FP digital products and services.



Specifications

28" L x 13.6" D x 11.8" H Dimensions Expandable catch tray length 12.6" - 17.5" 19.6 lbs. System weight Catch tray weight 2.2 lbs. Maximum letter thickness 0.40" Envelope sizes 3.5" x 5" to 10" x 14" Ink cartridge capacity (up to) 4,000 imprints <60 dB(A) Noise 4.3" color touchscreen Display

Certifications

CE, GS, CSA, Nemko, UL Listed Energy Star 3.0 USPS® IMI Approved Postage Solution

Connectivity

LAN or optional Wi-Fi adapter

Options

FP Parcel Shipping - multi carrier option Wi-Fi adapter FP Parcel Shipping 10 or 70 lb. capacity USB scale 4" x 6" shipping label printer





Learn more at: www.fp-usa.com/postbase-insight-semi-auto

© 2021 FP Mailing Solutions. All Rights Reserved. TM, SM and [®] denote trademarks or registered trademarks of Francotyp-Postalia, Inc. The FPTM logo and FPTM Mailing Solutions Product logos are trademarks or registered trademarks of Francotyp-Postalia, Inc. BR2033